

# SAFETY DATA SHEET

Version 8.12  
Revision Date 08.03.2024  
Print Date 12.07.2024

---

## SECTION 1: Identification of the substance/mixture and of the company/undertaking

### 1.1 Product identifiers

Product name : Toluene for analysis EMSURE®  
ACS,ISO,Reag. Ph Eur

Product Number : 1.08325  
Catalogue No. : 108325  
Brand : Millipore  
CAS-No. : 108-88-3

### 1.2 Other means of identification

No data available

### 1.3 Relevant identified uses of the substance or mixture and uses advised against

Identified uses : Reagent for analysis, Chemical production

### 1.4 Details of the supplier of the safety data sheet

Company : Merck Life Science Pty Ltd  
Ground Floor, Building 1, 885 Mountain Highway  
BAYSWATER VIC 3153  
AUSTRALIA

Telephone : +61 1800 800 097  
E-mail address : customersupport.anz@merckgroup.com

### 1.5 Emergency telephone

Emergency Phone # : Free call (24/7): 1800 862 115  
Int'l (24/7): +61 2 9037 2994  
(CHEMTREC)

---

## SECTION 2: Hazards identification

### 2.1 GHS Classification

Flammable liquids (Category 2), H225  
Skin corrosion/irritation (Category 2), H315  
Reproductive toxicity (Category 2), H361  
Specific target organ toxicity - single exposure (Category 3), Central nervous system, H336  
Specific target organ toxicity - repeated exposure, Inhalation (Category 2), Central nervous system, H373  
Aspiration hazard (Category 1), H304

For the full text of the H-Statements mentioned in this Section, see Section 16.

## 2.2 GHS Label elements, including precautionary statements

Pictogram



Signal Word

Danger

Hazard Statements

H225 Highly flammable liquid and vapor.  
H304 May be fatal if swallowed and enters airways.  
H315 Causes skin irritation.  
H336 May cause drowsiness or dizziness.  
H361 Suspected of damaging fertility or the unborn child.  
H373 May cause damage to organs (Central nervous system) through prolonged or repeated exposure if inhaled.

Precautionary Statements

Prevention

P201 Obtain special instructions before use.  
P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.  
P233 Keep container tightly closed.  
P260 Do not breathe mist or vapors.  
P264 Wash skin thoroughly after handling.  
P280 Wear protective gloves/ protective clothing/ eye protection/ face protection.

Response

P301 + P310 IF SWALLOWED: Immediately call a POISON CENTER/ doctor.  
P303 + P361 + P353 IF ON SKIN (or hair): Take off immediately all contaminated clothing. Rinse skin with water.  
P331 Do NOT induce vomiting.  
P370 + P378 In case of fire: Use dry sand, dry chemical or alcohol-resistant foam to extinguish.

## 2.3 Other hazards - none

### SECTION 3: Composition/information on ingredients

Substance / Mixture : Substance

#### 3.1 Substances

Formula : C<sub>7</sub>H<sub>8</sub>  
Molecular weight : 92.14 g/mol  
CAS-No. : 108-88-3  
EC-No. : 203-625-9  
Index-No. : 601-021-00-3

#### Hazardous ingredients

Component	Classification	Concentration
<b>Toluene</b>	Flam. Liq. 2; Skin Corr./Irrit. 2; Repr. 2;	<= 100 %

	STOT SE 3; STOT RE 2; Asp. Tox. 1; H225, H315, H361, H336, H373, H304 Concentration limits: 20 %: STOT SE 3, H336;	
--	--	--

For the full text of the H-Statements mentioned in this Section, see Section 16.

---

## SECTION 4: First aid measures

### 4.1 Description of first-aid measures

#### General advice

Show this material safety data sheet to the doctor in attendance.

#### If inhaled

After inhalation: fresh air. Call in physician.

#### In case of skin contact

In case of skin contact: Take off immediately all contaminated clothing. Rinse skin with water/ shower. Consult a physician.

#### In case of eye contact

After eye contact: rinse out with plenty of water. Call in ophthalmologist. Remove contact lenses.

#### If swallowed

After swallowing: caution if victim vomits. Risk of aspiration! Keep airways free. Pulmonary failure possible after aspiration of vomit. Call a physician immediately.

### 4.2 Most important symptoms and effects, both acute and delayed

The most important known symptoms and effects are described in the labelling (see section 2.2) and/or in section 11

### 4.3 Indication of any immediate medical attention and special treatment needed

No data available

---

## SECTION 5: Firefighting measures

### 5.1 Extinguishing media

#### Suitable extinguishing media

Foam Carbon dioxide (CO<sub>2</sub>) Dry powder

#### Unsuitable extinguishing media

For this substance/mixture no limitations of extinguishing agents are given.

### 5.2 Special hazards arising from the substance or mixture

Carbon oxides

Combustible.

Pay attention to flashback.

Vapors are heavier than air and may spread along floors.

Development of hazardous combustion gases or vapours possible in the event of fire.

Forms explosive mixtures with air at ambient temperatures.

### 5.3 Advice for firefighters

Stay in danger area only with self-contained breathing apparatus. Prevent skin contact by keeping a safe distance or by wearing suitable protective clothing.

### 5.4 Further information

Remove container from danger zone and cool with water. Prevent fire extinguishing water from contaminating surface water or the ground water system.

---

## SECTION 6: Accidental release measures

### 6.1 Personal precautions, protective equipment and emergency procedures

Advice for non-emergency personnel: Do not breathe vapors, aerosols. Avoid substance contact. Ensure adequate ventilation. Keep away from heat and sources of ignition. Evacuate the danger area, observe emergency procedures, consult an expert. For personal protection see section 8.

### 6.2 Environmental precautions

Do not let product enter drains. Risk of explosion.

### 6.3 Methods and materials for containment and cleaning up

Cover drains. Collect, bind, and pump off spills. Observe possible material restrictions (see sections 7 and 10). Take up carefully with liquid-absorbent material (e.g. Chemizorb®). Dispose of properly. Clean up affected area.

### 6.4 Reference to other sections

For disposal see section 13.

---

## SECTION 7: Handling and storage

### 7.1 Precautions for safe handling

#### Advice on safe handling

Work under hood. Do not inhale substance/mixture. Avoid generation of vapours/aerosols.

#### Advice on protection against fire and explosion

Keep away from open flames, hot surfaces and sources of ignition. Take precautionary measures against static discharge.

#### Hygiene measures

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

For precautions see section 2.2.

### 7.2 Conditions for safe storage, including any incompatibilities

#### Storage conditions

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat and sources of ignition.

Recommended storage temperature see product label.

#### Storage class

Storage class (TRGS 510): 3: Flammable liquids

### 7.3 Specific end use(s)

Apart from the uses mentioned in section 1.3 no other specific uses are stipulated.

## SECTION 8: Exposure controls/personal protection

### 8.1 Control parameters

#### Ingredients with workplace control parameters

Component	CAS-No.	Value	Control parameters	Basis
Toluene	108-88-3	TWA	50 ppm 191 mg/m <sup>3</sup>	Australia. Workplace Exposure Standards for Airborne Contaminants.
	Remarks	Skin absorption		
		STEL	150 ppm 574 mg/m <sup>3</sup>	Australia. Workplace Exposure Standards for Airborne Contaminants.
		Skin absorption		

#### Derived No Effect Level (DNEL)

Application Area	Routes of exposure	Health effect	Value
Workers	Inhalation	Acute systemic effects	384 mg/m <sup>3</sup>
Workers	Inhalation	Acute local effects	384 mg/m <sup>3</sup>
Workers	Skin contact	Long-term systemic effects	384mg/kg BW/d
Workers	Inhalation	Long-term systemic effects	192 mg/m <sup>3</sup>
Workers	Inhalation	Long-term local effects	192 mg/m <sup>3</sup>
Consumers	Inhalation	Acute systemic effects	226 mg/m <sup>3</sup>
Consumers	Inhalation	Acute local effects	226 mg/m <sup>3</sup>
Consumers	Skin contact	Long-term systemic effects	226mg/kg BW/d
Consumers	Inhalation	Long-term systemic effects	56.5 mg/m <sup>3</sup>
Consumers	Ingestion	Long-term systemic effects	8.13mg/kg BW/d

#### Predicted No Effect Concentration (PNEC)

Compartment	Value
Soil	2.89 mg/kg
Sea water	0.68 mg/l
Fresh water	0.68 mg/l
Sea sediment	16.39 mg/kg
Fresh water sediment	16.39 mg/kg
Sewage treatment plant	13.61 mg/l
Aquatic intermittent release	0.68 mg/l

### 8.2 Exposure controls

#### Appropriate engineering controls

Immediately change contaminated clothing. Apply preventive skin protection. Wash hands and face after working with substance.

## Personal protective equipment

### Eye/face protection

Use equipment for eye protection tested and approved under appropriate government standards such as NIOSH (US) or EN 166(EU). Safety glasses

### Skin protection

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Full contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

This recommendation applies only to the product stated in the safety data sheet, supplied by us and for the designated use. When dissolving in or mixing with other substances and under conditions deviating from those stated in EN 16523-1 please contact the supplier of CE-approved gloves (e.g. KCL GmbH, D-36124 Eichenzell, Internet: [www.kcl.de](http://www.kcl.de)).

Splash contact

Material: Viton®

Minimum layer thickness: 0.7 mm

Break through time: 480 min

Material tested: Vitoject® (KCL 890 / Aldrich Z677698, Size M)

### Body Protection

Flame retardant antistatic protective clothing.

### Respiratory protection

required when vapours/aerosols are generated. Our recommendations on filtering respiratory protection are based on the following standards: DIN EN 143, DIN 14387 and other accompanying standards relating to the used respiratory protection system.

### Control of environmental exposure

Do not let product enter drains. Risk of explosion.

---

## SECTION 9: Physical and chemical properties

### 9.1 Information on basic physical and chemical properties

- |                                 |                                   |
|---------------------------------|-----------------------------------|
| a) Physical state               | liquid                            |
| b) Color                        | colorless                         |
| c) Odor                         | benzene-like                      |
| d) Melting point/freezing point | Melting point/range: -95 - -93 °C |
| e) Initial boiling point        | 110.6 °C at 1,013 hPa             |

	and boiling range	
f)	Flammability (solid, gas)	No data available
g)	Upper/lower flammability or explosive limits	Upper explosion limit: 7.1 %(V) Lower explosion limit: 1.2 %(V)
h)	Flash point	4.4 °C - closed cup
i)	Autoignition temperature	No data available
j)	Decomposition temperature	No data available
k)	pH	Not applicable
l)	Viscosity	Viscosity, kinematic: No data available Viscosity, dynamic: 0.56 mPa.s at 25 °C
m)	Water solubility	0.58 g/l at 25 °C - partly soluble
n)	Partition coefficient: n-octanol/water	log Pow: 2.73 at 20 °C - Bioaccumulation is not expected.
o)	Vapor pressure	30.88 hPa at 21.1 °C
p)	Density	0.87 g/cm <sup>3</sup> at 20 °C
	Relative density	No data available
q)	Relative vapor density	No data available
r)	Particle characteristics	No data available
s)	Explosive properties	No data available
t)	Oxidizing properties	none

## 9.2 Other safety information

Conductivity	< 0.01 µS/cm
Surface tension	27.73 mN/m at 0.516g/l at 25 °C
Relative vapor density	3.18

---

## SECTION 10: Stability and reactivity

### 10.1 Reactivity

Vapors may form explosive mixture with air.  
Vapors may form explosive mixture with air.

### 10.2 Chemical stability

The product is chemically stable under standard ambient conditions (room temperature) .

The product is chemically stable under standard ambient conditions (room temperature) .

### **10.3 Possibility of hazardous reactions**

Risk of explosion with:

fuming sulfuric acid

Nitric acid

silver

perchlorates

nitrogen dioxide

nonmetallic halides

halogen-halogen compounds

uranium hexafluoride

organic nitro compounds

Violent reactions possible with:

Strong acids

Strong oxidizing agents

sulfur

with

Heat.

### **10.4 Conditions to avoid**

Warming.

Warming.

### **10.5 Incompatible materials**

No data available

### **10.6 Hazardous decomposition products**

In the event of fire: see section 5

---

## **SECTION 11: Toxicological information**

### **11.1 Information on toxicological effects**

#### **Acute toxicity**

LD50 Oral - Rat - male - 5,580 mg/kg

(Directive 67/548/EEC, Annex V, B.1.)

LC50 Inhalation - Rat - male - 4 h - 25.7 mg/l - vapor

(OECD Test Guideline 403)

LD50 Dermal - Rabbit - male - > 5,000 mg/kg

Remarks: (ECHA)

#### **Skin corrosion/irritation**

Skin - Rabbit

Result: irritating - 4 h

(Regulation (EC) No. 440/2008, Annex, B.4)

#### **Serious eye damage/eye irritation**

Eyes - Rabbit

Result: No eye irritation

(OECD Test Guideline 405)

**Respiratory or skin sensitization**

Maximization Test - Guinea pig

Result: negative

(Regulation (EC) No. 440/2008, Annex, B.6)

**Germ cell mutagenicity**

Test Type: In vitro mammalian cell gene mutation test

Test system: Mouse lymphoma test

Metabolic activation: with and without metabolic activation

Method: OECD Test Guideline 476

Result: negative

Test Type: Ames test

Test system: S. typhimurium

Metabolic activation: with and without metabolic activation

Method: Regulation (EC) No. 440/2008, Annex, B.13/14 (Ames test)

Result: negative

Test Type: Chromosome aberration test

Species: Rat

Cell type: Bone marrow

Application Route: Intraperitoneal

Result: negative

Remarks: (ECHA)

**Carcinogenicity**

No data available

**Reproductive toxicity**

Suspected of damaging the unborn child.

**Specific target organ toxicity - single exposure**

Inhalation - May cause drowsiness or dizziness. - Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

**Specific target organ toxicity - repeated exposure**

Inhalation - May cause damage to organs through prolonged or repeated exposure.

- Central nervous system

Remarks: Classified according to Regulation (EU) 1272/2008, Annex VI (Table 3.1/3.2)

**Aspiration hazard**

Aspiration may cause pulmonary edema and pneumonitis.

**11.2 Additional Information**

Repeated dose toxicity - Rat - male and female - Oral - 13 Weeks - NOAEL (No observed adverse effect level) - 625 mg/kg - LOAEL (Lowest observed adverse effect level) - 1,250 mg/kg

Drowsiness, irritant effects, Dizziness, Convulsions, Headache, Nausea, Vomiting, Circulatory collapse, somnolence, inebriation, Unconsciousness, respiratory arrest, CNS disorders, respiratory paralysis, death

To the best of our knowledge, the chemical, physical, and toxicological properties have not been thoroughly investigated.

---

## SECTION 12: Ecological information

### 12.1 Toxicity

Toxicity to fish	flow-through test LC50 - Oncorhynchus kisutch (coho salmon) - 5.5 mg/l - 96 h Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates	EC50 - Ceriodaphnia dubia (water flea) - 3.78 mg/l - 48 h (US-EPA)
Toxicity to bacteria	static test EC50 - Bacteria - 84 mg/l - 24 h Remarks: (ECHA)
Toxicity to fish(Chronic toxicity)	flow-through test NOEC - Oncorhynchus kisutch (coho salmon) - 1.39 mg/l - 40 d Remarks: (ECHA)
Toxicity to daphnia and other aquatic invertebrates(Chronic toxicity)	NOEC - Ceriodaphnia dubia (water flea) - 0.74 mg/l - 7 d (US-EPA)

### 12.2 Persistence and degradability

Biodegradability	aerobic - Exposure time 20 d Result: 86 % - Readily biodegradable. Remarks: (IUCLID)
------------------	--

### 12.3 Bioaccumulative potential

Bioaccumulation	Leuciscus idus (Golden orfe) - 3 d - 0.05 mg/l(Toluene)
	Bioconcentration factor (BCF): 90

### 12.4 Mobility in soil

No data available

### 12.5 Results of PBT and vPvB assessment

PBT/vPvB assessment not available as chemical safety assessment not required/not conducted

### 12.6 Endocrine disrupting properties

No data available

### 12.7 Other adverse effects

No data available

---

**SECTION 13: Disposal considerations****13.1 Waste treatment methods****Product**

Waste material must be disposed of in accordance with the national and local regulations. Leave chemicals in original containers. No mixing with other waste. Handle uncleaned containers like the product itself.

---

**SECTION 14: Transport information****14.1 UN number**

ADR/RID: 1294                      IMDG: 1294                      IATA-DGR: 1294

**14.2 UN proper shipping name**

ADR/RID:                      TOLUENE  
IMDG:                      TOLUENE  
IATA-DGR:                      Toluene

**14.3 Transport hazard class(es)**

ADR/RID: 3                      IMDG: 3                      IATA-DGR: 3

**14.4 Packaging group**

ADR/RID: II                      IMDG: II                      IATA-DGR: II

**14.5 Environmental hazards**

ADR/RID: no                      IMDG Marine pollutant: no                      IATA-DGR: no

**14.6 Special precautions for user**

None

**14.7 Incompatible materials****Other regulations**

Hazchem Code                      : 3YE

---

**SECTION 15: Regulatory information****15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture**

Therapeutic Goods (Poisons Standard)                      : No poison schedule number allocated  
Instrument

---

**SECTION 16: Other information**

-

**Full text of H-Statements referred to under sections 2 and 3.**

H225                      Highly flammable liquid and vapor.  
H304                      May be fatal if swallowed and enters airways.

Millipore- 1.08325

Page 11 of 12

The life science business of Merck operates as MilliporeSigma in the US and Canada



H315	Causes skin irritation.
H336	May cause drowsiness or dizziness.
H361	Suspected of damaging fertility or the unborn child.
H373	May cause damage to organs through prolonged or repeated exposure if inhaled.

**Further information**

The information is believed to be correct but is not exhaustive and will be used solely as a guideline, which is based on current knowledge of the chemical substance or mixture and is applicable to appropriate safety precautions for the product. It does not represent any guarantee of the properties of the product. Sigma-Aldrich Corporation and its Affiliates shall not be held liable for any damage resulting from handling or from contact with the above product. See [www.sigma-aldrich.com](http://www.sigma-aldrich.com) and/or the reverse side of invoice or packing slip for additional terms and conditions of sale.

Copyright 2020 Sigma-Aldrich Co. LLC. License granted to make unlimited paper copies for internal use only.

The branding on the header and/or footer of this document may temporarily not visually match the product purchased as we transition our branding. However, all of the information in the document regarding the product remains unchanged and matches the product ordered. For further information please contact [mlsbranding@sial.com](mailto:mlsbranding@sial.com).