

Classified as hazardous according to criteria of EPA New Zealand

Section 1 - Identification

Product Name 2-Propanol

Product Code	ACR14932, ACR16788, ACR18413, ACR32696, , ACR32727, ACR38391, ACR38971, ACR38971, ACR42383, AJA2323, AJA425, AJA426, AJA593, AJA946, ASC-DISOPR, BSPPL512, BSPPL865, FSBA451, FSBA461, FSBA464, FSBP2618, FSBP/7490, FSBP/7500, FSBP/7501, FSBP/7503, FSBP/7507, FSBP/7508, FSBP/7509, FSBP/7555, PAUISOPROPANOL, TCHASL205, TCHPROPAN2OL
Address	Thermo Fisher Scientific New Zealand Ltd 244 Bush Road, Albany, Auckland, New Zealand
Emergency Tel.	CHEMTREC® 09 980 6780 or +64 9 980 6780
Telephone / Fax Numbers	Tel: 09 980 6700 Fax: 09 980 6788
E-mail address	<u>NZinfo@thermofisher.com</u>

Recommended Use Laboratory chemicals.

Section 2 - Hazard(s) Identification

Classification under Work Safe New Zealand

- 3.1B - Flammable liquids: high hazard
- 6.1E - Substances that are acutely toxic (Oral)
- 6.3B - Substances that are mildly irritating to the skin
- 6.4A - Substances that are irritating to the eye
- 6.9B - Substances that are harmful to human target organs or systems

Classified as hazardous according to criteria of EPA New Zealand

HSNO Approval Number HSR001180

GHS Classification

Physical hazards

Flammable liquids Category 2

Health hazards

Acute Oral Toxicity	Category 5
Skin Corrosion/Irritation	Category 3
Serious Eye Damage/Eye Irritation	Category 2
Specific target organ toxicity - (single exposure)	Category 3

Environmental hazards

Based on available data, the classification criteria are not met

Label Elements

Signal Word

Danger

Hazard Statements

H225 - Highly flammable liquid and vapor
 H303 - May be harmful if swallowed
 H316 - Causes mild skin irritation
 H319 - Causes serious eye irritation
 H336 - May cause drowsiness or dizziness

Precautionary Statements

P210 - Keep away from heat/sparks/open flames/hot surfaces. - No smoking
 P233 - Keep container tightly closed
 P240 - Ground/bond container and receiving equipment
 P242 - Use non-sparking tools
 P243 - Take precautionary measures against static discharge
 P261 - Avoid breathing dust/fume/gas/mist/vapors/spray
 P264 - Wash face, hands and any exposed skin thoroughly after handling
 P271 - Use only outdoors or in a well-ventilated area
 P280 - Wear protective gloves/protective clothing/eye protection/face protection
 P303 + P361 + P353 - IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower
 P304 + P340 - IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing
 P305 + P351 + P338 - IF IN EYES: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing
 P312 - Call a POISON CENTER or doctor/physician if you feel unwell
 P370 + P378 - In case of fire: Use CO₂, dry chemical or foam for extinction
 P403 + P233 - Store in a well-ventilated place. Keep container tightly closed
 P501 - Dispose of contents/ container to an approved waste disposal plant

Other information

No information available

Section 3 - Composition and Information on Ingredients

Component	CAS-No	Weight %
Isopropyl alcohol	67-63-0	99-100

Section 4 - First Aid Measures

Inhalation	Remove to fresh air.
Ingestion	Clean mouth with water and drink afterwards plenty of water.
Skin Contact	Wash off immediately with soap and plenty of water while removing all contaminated clothes and shoes.
Eye Contact	Rinse thoroughly with plenty of water for at least 15 minutes, lifting lower and upper eyelids.

	Consult a physician.
Self-Protection of the First Aider	Ensure that medical personnel are aware of the material(s) involved, take precautions to protect themselves and prevent spread of contamination.
First Aid Facilities	Eyewash, safety shower and washroom.
Most important symptoms and effects	Difficulty in breathing. . Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting
Notes to Physician	Treat symptomatically.

Section 5 - Fire Fighting Measures

Suitable Extinguishing Media

Water mist may be used to cool closed containers.

Extinguishing media which must not be used for safety reasons

No information available.

Hazardous Combustion Products

Specific Hazards Arising from the Chemical

Flammable. Containers may explode when heated. Vapors may form explosive mixtures with air. Vapors may travel to source of ignition and flash back.

Special protective equipment and precautions for fire fighters

As in any fire, wear self-contained breathing apparatus pressure-demand, MSHA/NIOSH (approved or equivalent) and full protective gear.

Section 6 - Accidental Release Measures

Emergency procedures

Remove all sources of ignition. Take precautionary measures against static discharges.

Environmental Precautions

See Section 12 for additional Ecological Information.

Methods for Containment and Clean Up

Remove all sources of ignition. Use spark-proof tools and explosion-proof equipment.

Reference to Other Sections

Refer to protective measures listed in Sections 8 and 13.

Section 7 - Handling and Storage

Precautions for Safe Handling

Keep away from open flames, hot surfaces and sources of ignition. Use only non-sparking tools. To avoid ignition of vapors by static electricity discharge, all metal parts of the equipment must be grounded. Take precautionary measures against static discharges.

Conditions for Safe Storage, Including any Incompatibilities

Keep container tightly closed in a dry and well-ventilated place. Keep away from heat, sparks and flame.

AS/NZS 2243.10:2004, Safety in laboratories - Storage of chemicals

AS 1940-2004 - The storage and handling of flammable and combustible liquids does not apply to this product. It is covered by the ADG Code Class 3 exclusion clause (i.e. SP No 144 An aqueous solution containing not more than 24% alcohol by volume is not subject to the ADG Code, AS1940 section 1.2). Refer to AS1940 to ensure compliance of individual storage and handling facilities.

Section 8 - Exposure Controls and Personal Protection

Exposure limits

NZ - Workplace Exposure Standards and Biological Exposure Indices (6th edition). New Zealand Department of Labor

Component	New Zealand WEL
Isopropyl alcohol	TWA: 400 ppm TWA: 983 mg/m ³ STEL: 500 ppm STEL: 1230 mg/m ³

Biological limit values

This product, as supplied, does not contain any hazardous materials with biological limits established by the region specific regulatory bodies

Engineering Measures

Ensure that eyewash stations and safety showers are close to the workstation location. Ensure adequate ventilation, especially in confined areas. Use explosion-proof electrical/ventilating/lighting/equipment. Wherever possible, engineering control measures such as the isolation or enclosure of the process, the introduction of process or equipment changes to minimise release or contact, and the use of properly designed ventilation systems, should be adopted to control hazardous materials at source

Personal protective equipment**Eye Protection**

Goggles (Australian/New Zealand Standard AS/NZS 1337 - Eye protectors for Industrial applications)

Hand Protection

Protective gloves

Glove material	Breakthrough time	Glove thickness	AUS/NZ Standard	Glove comments
Nitrile rubber, Neoprene, Natural rubber, PVC.	See manufacturers recommendations	-	AS/NZS 2161.1	(minimum requirement)

Inspect gloves before use.

Please observe the instructions regarding permeability and breakthrough time which are provided by the supplier of the gloves. (Refer to manufacturer/supplier for information)

Ensure gloves are suitable for the task: Chemical compatability, Dexterity, Operational conditions, User susceptibility, e.g. sensitisation effects, also take into consideration the specific local conditions under which the product is used, such as the danger of cuts, abrasion.

Remove gloves with care avoiding skin contamination.

Skin and body protection

Long sleeved clothing

Respiratory Protection

Use an AS/NZS 1716 approved respirator if exposure limits are exceeded or if irritation or other symptoms are experienced. To protect the wearer, respiratory protective equipment must be the correct fit and be used and maintained in line with AS/NZS 1715 on the use and maintenance of respiratory protective devices

Recommended Filter type:

Organic gases and vapours filter Type A Brown conforming to EN14387 (or AUS/NZ equivalent)

Recommended half mask:-

Valve filtering: EN405 or Half mask: EN140 plus filter, EN 141 (or AUS/NZ equivalent)
When RPE is used a face piece Fit Test should be conducted

Hygiene Measures

Handle in accordance with good industrial hygiene and safety practice.

Environmental exposure controls

No information available.

Section 9 - Physical and Chemical Properties

Information on basic physical and chemical properties

Appearance
Physical State

Clear
Liquid

Odor
Odor Threshold
pH
Melting Point/Range
Softening Point
Boiling Point/Range
Flash Point

No information available
No data available
Not applicable
-89 °C / -128.2 °F
No data available
82 °C / 179.6 °F
11 °C / 51.8 °F

Method - No information available

Evaporation Rate	No data available	
Flammability (solid,gas)	Not applicable	Liquid
Explosion Limits	No data available	
Vapor Pressure	No data available	
Vapor Density	No data available	(Air = 1.0)
Specific Gravity / Density	No data available	
Bulk Density	Not applicable	Liquid
Water Solubility	Soluble in water	
Solubility in other solvents	No information available	
Partition Coefficient (n-octanol/water)		
Component	log Pow	
Isopropyl alcohol	0.05	
Autoignition Temperature	No data available	
Decomposition Temperature	No data available	
Viscosity	No data available	
Explosive Properties	No information available	Vapors may form explosive mixtures with air
Oxidizing Properties	No information available	
Other information		
Molecular Formula	C3H8O	
Molecular Weight	60.1	

Section 10 - Stability and Reactivity

Reactivity	None known, based on information available
Stability	Stable under normal conditions.
Conditions to Avoid	Keep away from open flames, hot surfaces and sources of ignition.
Hazardous Decomposition Products	None under normal use conditions.
Hazardous Polymerization	No information available.

Section 11 - Toxicological Information

Information on Toxicological Effects

Product Information

(a) acute toxicity;

Oral	Based on available data, the classification criteria are not met
Dermal	Based on available data, the classification criteria are not met
Inhalation	Based on available data, the classification criteria are not met

Component	LD50 Oral	LD50 Dermal	LC50 Inhalation
Isopropyl alcohol	4396 mg/kg (Rat)	12800 mg/kg (Rat)	72.6 mg/L (Rat) 4 h

(b) skin corrosion/irritation; Based on available data, the classification criteria are not met

(c) serious eye damage/irritation; Category 2

(d) respiratory or skin sensitization;

Respiratory	Based on available data, the classification criteria are not met
Skin	Based on available data, the classification criteria are not met

(e) germ cell mutagenicity; Based on available data, the classification criteria are not met

(f) carcinogenicity;	Based on available data, the classification criteria are not met
(g) reproductive toxicity;	There are no known carcinogenic chemicals in this product
(h) STOT-single exposure;	Based on available data, the classification criteria are not met Category 3
(i) STOT-repeated exposure;	Based on available data, the classification criteria are not met
Target Organs	None known.
(j) aspiration hazard;	Based on available data, the classification criteria are not met

Symptoms / effects, both acute and delayed Inhalation of high vapor concentrations may cause symptoms like headache, dizziness, tiredness, nausea and vomiting

Section 12 - Ecological Information

Ecotoxicity effects

Component	Freshwater Fish	Water Flea	Freshwater Algae	Microtox
Isopropyl alcohol	LC50: = 9640 mg/L, 96h flow-through (Pimephales promelas) LC50: > 1400000 µg/L, 96h (Lepomis macrochirus) LC50: = 11130 mg/L, 96h static (Pimephales promelas)	13299 mg/L EC50 = 48 h 9714 mg/L EC50 = 24 h	EC50: > 1000 mg/L, 72h (Desmodesmus subspicatus) EC50: > 1000 mg/L, 96h (Desmodesmus subspicatus)	= 35390 mg/L EC50 Photobacterium phosphoreum 5 min

Persistence and Degradability

Persistence

Persistence is unlikely, based on information available.

Bioaccumulative Potential

Bioaccumulation is unlikely

Component	log Pow	Bioconcentration factor (BCF)
Isopropyl alcohol	0.05	No data available

Mobility

The product contains volatile organic compounds (VOC) which will evaporate easily from all surfaces. Will likely be mobile in the environment due to its volatility. Disperses rapidly in air

Endocrine Disruptor Information

This product does not contain any known or suspected endocrine disruptors

Persistent Organic Pollutant

This product does not contain any known or suspected substance

Ozone Depletion Potential

This product does not contain any known or suspected substance

Section 13 - Disposal Considerations

Waste from Residues/Unused Products

Do not allow into drains or watercourses or dispose of where ground or surface waters may be affected. Wastes, including emptied containers, are controlled wastes and should be disposed of in accordance with all federal, E.P.A., state and local regulations. Assure conformity with all applicable regulations.

Contaminated Packaging

Dispose of this container to hazardous or special waste collection point. Empty containers retain product residue, (liquid and/or vapor), and can be dangerous. Keep product and empty container away from heat and sources of ignition.

Other Information

Disposal agencies or waste contractors must comply with the New Zealand Hazardous Substances (Disposal) Regulations. Waste codes should be assigned by the user based on the application for which the product was used. Do not flush to sewer. Can be landfilled or incinerated, when in compliance with local regulations.

Section 14 - Transport Information

IMDG/IMO

UN-No UN1219
 Proper Shipping Name ISOPROPANOL
 Hazard Class 3
 Packing Group II

NZS 5433:2012

UN-No UN1219
 Proper Shipping Name ISOPROPANOL
 Hazard Class 3
 Packing Group II

Component	Hazchem Code
Isopropyl alcohol 67-63-0 (99-100)	1Z

IATA

UN-No UN1219
 Proper Shipping Name ISOPROPANOL
 Hazard Class 3
 Packing Group II

Environmental hazards No hazards identified

Special Precautions No special precautions required

Additional information None known

Section 15 - Regulatory Information

Safety, health and environmental regulations/legislation specific for the substance or mixture

Component	HSNO Approval Number
Isopropyl alcohol	HSR001180

International Inventories X = listed

Component	NZIoC	AICS	EINECS	ELINCS	TSCA	DSL	NDSL	PICCS	ENCS	IECSC	KECL
Isopropyl alcohol	X	X	200-661-7	-	X	X	-	X	X	X	KE-2936 3

Prohibition or notification/licensing requirements Shown below are details of specific prohibition/notifications or licencing requirements when they apply.

Section 16 - Other Information

This safety data sheet complies with the requirements of WorkSafe New Zealand Regulations

Legend

AICS - Australian Inventory of Chemical Substances
TSCA - United States Toxic Substances Control Act Section 8(b) Inventory
DSL/NDSL - Canadian Domestic Substances List/Non-Domestic Substances List
IECSC - Chinese Inventory of Existing Chemical Substances
PICCS - Philippines Inventory of Chemicals and Chemical Substances
TWA - Time Weighted Average
IARC - International Agency for Research on Cancer
ICAO/IATA - International Civil Aviation Organization/International Air Transport Association
MARPOL - International Convention for the Prevention of Pollution from

NZIoC - New Zealand Inventory of Chemicals
EINECS/ELINCS - European Inventory of Existing Commercial Chemical Substances/EU List of Notified Chemical Substances
ENCS - Japanese Existing and New Chemical Substances
KECL - Korean Existing and Evaluated Chemical Substances
CAS - Chemical Abstracts Service
ACGIH - American Conference of Governmental Industrial Hygienists
 Predicted No Effect Concentration (PNEC)
IMO/IMDG - International Maritime Organization/International Maritime Dangerous Goods Code

Ships

NZS 5433:2012 - Transport of Dangerous Goods on Land

LD50 - Lethal Dose 50%

EC50 - Effective Concentration 50%

WEL - Workplace Exposure Limit

DNEL - Derived No Effect Level

POW - Partition coefficient Octanol:Water

vPvB - very Persistent, very Bioaccumulative

VOC (volatile organic compound)

ADG Australian Code for the Transport of Dangerous Goods by Road and Rail

OECD - Organisation for Economic Co-operation and Development

LC50 - Lethal Concentration 50%

ATE - Acute Toxicity Estimate

RPE - Respiratory Protective Equipment

NOEC - No Observed Effect Concentration

BCF - Bioconcentration factor

PBT - Persistent, Bioaccumulative, Toxic

Key literature references and sources for data

Suppliers safety data sheet, Chemadvisor - LOLI, Merck index, RTECS

Training Advice

Chemical hazard awareness training, incorporating labelling, Safety Data Sheets (SDS), Personal Protective Equipment (PPE) and hygiene.

Use of personal protective equipment, covering appropriate selection, compatibility, breakthrough thresholds, care, maintenance, fit and standards.

First aid for chemical exposure, including the use of eye wash and safety showers.

Revision Date 04-Jul-2020
Revision Summary Not applicable.

Disclaimer

The information provided in this Safety Data Sheet is correct to the best of our knowledge, information and belief at the date of its publication. The information given is designed only as a guidance for safe handling, use, processing, storage, transportation, disposal and release and is not to be considered a warranty or quality specification. The information relates only to the specific material designated and may not be valid for such material used in combination with any other materials or in any process, unless specified in the text

End of Safety Data Sheet