

Product Specifications

FlashLink Certified Alarm Thermometer

Internal Sensor Range	14°F to 122°F (-10°C to 50°C)
External Probe Range	-58°F to 158°F (-50°C to 70°C)
Accuracy	±1.0°F from 14°F to 77°F (±.5°C from -10°C to 25°C); ±2.0°F above 77°F (±1.0°C above 25°C) ±2.0°F below 14°F (±1.0°C below -10°C)
Sampling Rate	10 seconds
Display Resolution	0.1°F/°C
Display Size	1.8in W x 0.87in H (46mm W x 22mm H)
Instrument Size	3.15in W x 2.05in H x 0.67in D (80mm W x 52mm H x 17mm D)
Case Material	ABS polymer, resistant to chemicals and high impact
External Probe Type/Size	Stainless Steel, 0.7in L x 0.2in Dia (17.8mm L x 5mm Dia)
External Sensor Bottle	Polystyrene with PE cap, 1.6in L x 0.79in Dia (41mm L x 20mm Dia)
External Sensor Buffer	Propylene glycol (GRAS classified – Generally Recognized As Safe)
External Sensor Cable	9.84ft x 0.08in Dia (3 meters x 2mm Dia)
Battery	Coin Cell Lithium Battery, user replaceable
Battery Life	10,000 hours of continuous use
Certification	CE mark, NIST traceable, WEEE



Models

12215	Includes Manufacturer's Certificate of Compliance traceable to NIST
12224	Includes NIST Calibration Certificate & Manufacturer's Certificate of Compliance
12225	Includes ISO 17025 Calibration Certificate & Manufacturer's Certificate of Compliance

- Ideal for monitoring vaccines and common fluids stored in refrigerators, freezers, and cold holding display cases
- More than 1 year of continuous monitoring
- Internal sensor for ambient air temperature
- External sensor with high/low alarm setting
- Switchable internal/external temperature display
- Glycol buffered probe emulates products and prevents false alarms during normal use
- Minimum/Maximum memory stores lowest/highest readings
- Audible alarm for temperature excursions
- Jumbo LCD with back light
- Switchable °F/°C scale
- Magnetic attachment and fold-away stand

SS0122 16B1

